

100% Electric | Driver Optional | Data-Driven

| Power | | XLR | LR |
|-------------------|---------|----------|---------|
| Peak Motor Power | hp (kW) | 70 | (52) |
| Rated Motor Power | hp (kW) | 40 | (30) |
| Run Time | hrs | est. 14* | est. 7* |

*varies based on farm, operation, and implement

| Drive Train | |
|------------------|--------------------------------|
| Туре | 4 Wheel Drive |
| Transmission | Push Button Transmission |
| Number of Speeds | 9F / 3R |
| Clutch Type | Wet |
| Clutch Actuation | Automated Electro-hydraulic |
| Brake Type | Wet, Independent |
| Brake Actuation | Mechanical / Electro-hydraulic |

| Power Take-Off | | |
|-----------------|---------|-------------------|
| PTO Power | hp (kW) | 40 (30) |
| PTO Speed | rpm | 540 |
| PTO Location | | Rear |
| PTO Clutch Type | | Wet |
| PTO Actuation | | Electro-hydraulic |

| Hydraulics | | |
|--------------------------------|-------------|--------------------------|
| Type | | Closed Center |
| Pump Rated Output | gpm (I/min) | 19.8 (75) |
| Rated Flow (for Constant Flow) | gpm (I/min) | 12.0 (45) |
| Rear Remote Valves | | 2 SCVs + 1 Constant Flow |

| Implement Interface | | |
|----------------------------|----------|-----------------------|
| 3-Point Hitch | | CAT I/II |
| Hitch Lift Capacity | lbs (kg) | 2,200 (997) |
| Drawbar Type | | Swinging, 3 positions |
| Drawbar Towing Capacity | lbs (kg) | 5,500 (2,500) |
| Drawbar Max. Vertical Load | lbs (kg) | 1,100 (500) |
| Front Ballast Capacity | lbs (kg) | up to 528 (240) |

WWW.MONARCHTRACTOR.COM

| Tires | |
|-------------|----------------------|
| Tire Type | R1 AG |
| Front Tires | 200 / 70R16 Tubeless |
| Rear Tires | 11.2-24 Tubeless |

| Charging and Exportable Power | | XLR | LR |
|---------------------------------|-----|--------------|--------------|
| Charge Port | | J1772 Type 1 | (up to 80 A) |
| Charging Level | | AC Le | evel 2 |
| Charging Time (w/ 80 A Charger) | hrs | 5 | 2.5 |
| Charging Time (w/ 40 A Charger) | hrs | 10 | 5 |
| 220 VAC Power Outlet | | NEMA L6 | -30R (18A) |
| 110 VAC Power Outlet | | NEMA 5 | -15 (15A) |

| Roof | | |
|---------------------------------|--------|------------------|
| ROPS | | Rigid, 4-Post |
| LED Work Lights | | 8x (2x per side) |
| LED Work Light Brightness, each | lumens | 2,000 |

| Connectivity Modules | |
|----------------------|-------------------------------|
| WiFi | 802.11ac Dual Band |
| Cellular | 4G (LTE) Ready |
| Radio | Lora - 900 Mhz - 30 Dbi Ready |

| Dimensions | | |
|-------------------------------|----------|--|
| Overall Tractor Length | in (mm) | 146.7 (3,725) |
| Overall Tractor Height | in (mm) | 92.1 (2,340) |
| Minimum Tractor Width | in (mm) | 48.4 (1,230) |
| Roof Width | in (mm) | 51.8 (1,315) |
| Wheelbase | in (mm) | 85.0 (2,160) |
| Front Axle Clearance | in (mm) | 11.0 (280) |
| Front Track Width | in (mm) | 37.0 (939) |
| Rear Track Width (Adjustable) | in (mm) | 36.0 (916) 40.6 (1,030) 43.9 (1,116) 48.4 (1,230) |
| Turning Radius | ft (m) | 8.9 (2.7) |
| Base Weight | lbs (kg) | 5,750 (2,610) |

| Warranty | | |
|----------|-------------|------------|
| Tractor | years / hrs | 4 / 4,000* |
| Battery | years / hrs | 8 / 8,000 |

*extended warranty available for CORE customers



